CAPITAL B



Recessed module for burgess type ceilings


Also available for plasterboard, burgess and SAS type ceilings

I-Tech microprism optic provides excellent glare control with BS EN-12464 compliance



CAPITAL B





- Also available for plasterboard, burgess and SAS type
- I-Tech microprism optic provides excellent glare control with BS EN-12464 compliance

 • Suitable for office installations and general or task area
- Available in 3 standard sizes with bespoke, retro-fit versions available
- Gear options of DALI and Emergency
- Air handling for 40 litres/second option
- CRI: Ra>80
- Up to 120 lumens per Watt efficacy
- 50,000 hours lifetime
- Wieland 3/4 pole connector on rear of body for mains connection















Recessed module for burgess type ceilings

Order Code	Description	lm	W	lm/W	kg
CPB66MP300NW	25W - 4000K Microprism diffuser	3,000	25	120	5.55
CPB123MP300NW	28W - 4000K Microprism diffuser	3,000	28	107	6.55

Dimensions

Order Code	A (mm)	B (mm)	C (mm)
CPB66MP300NW	599	599	109
CPB123MP300NW	1199	299	109





CONSTRUCTION

- Pressed steel body
- Prismatic polycarbonate diffuser
- Supplied as standard with neutral white (4000K) LED

OPTIONS


D	Dimmable DALI
	Diffillable by the
M3	3 hours integrated emergency
	o modro imogration ormorgano,
A3	Emergency self test
/ 10	Littorgonoy don toot
D3	DALI self test
טט	

INSTALLATION NOTES

View or download the ceiling compatability

TO SPECIFY

Recessed module for burgess type ceilings as per Tamlite CAPITAL B range



Lighting for a Living

Tamlite Lighting Sales Centre

Tamlite Field Sales Centre, Park Farm Industrial Estate, Redditch, Worcestershire, B98 0HU

T. 01527 517 777E. sales@tamlite.co.ukW. tamlite.co.uk

Over 50 years lighting for a Living

As a UK manufacturer we have one of the widest lighting ranges across:





















Communal

Education

Emergency

Healthcare

Industrial

Office

Retail & Leisure

Sports

Urban

Warehouse & Logistics