CORNICE



Corner mounted profile is ideal for corridor and walkway areas

High quality aluminium extrusions

Suspended mounted option



Lighting for a Living

CORNICE





- Suspended mounted option
- Full range of gear options including DALI and emergency are available
- CRI: Ra>80
- Up to 111 lumens per Watt efficacy50,000 hours lifetime (L70/B50)









Corner light

Order Code	Description	lm	W	lm/W	kg
CORCM3240NW	23W - 4000K	2400	23	104	2.30
CORCM4300NW	28W - 4000K	3000	28	107	3.00
CORCM5420NW	38W - 4000K	4200	38	111	3.70

Dimensions

Order Code	A (mm)	B (mm)	C (mm)
CORCM3240NW	875	101	64
CORCM4300NW	1165	101	64
CORCM5420NW	1455	101	64



CONSTRUCTION

- Extruded aluminium body finished in white (RAL 9016)
- Opal polycarbonate diffuser
- Rear or 2 x side cable entry
- Supplied as standard with neutral white (4000K) LED

OPTIONS


M3	3 hours integrated emergency
A3	Auto self test
D3	DALI self test
D	DALI dimming control gear
WW	Warm white (3000K)
CW	Cool white (5000K)
MPRM	Micro-prism diffuser

INSTALLATION NOTES

Wall or ceiling fix base mounting, with rear or side cable entry

TO SPECIFY

Corner mounted light as per Tamlite CORNICE range



Lighting for a Living



Tamlite Lighting Sales Centre

Tamlite Field Sales Centre, Park Farm Industrial Estate, Redditch, Worcestershire, B98 0HU

T. 01527 517 777E. sales@tamlite.co.ukW. tamlite.co.uk

Over 50 years lighting for a Living

As a UK manufacturer we have one of the widest lighting ranges across:























Communal Education

n Em

Emergency

Healthcare

Industrial

Office

Retail & Leisure

Sports

Urban Warehouse & Logistics