

MICRO LED X L

High output LEDs for up to 16 metre mounting height

Ideal for industrial and commercial applications

Wide beam or narrow beam versions available





















MICRO LED XL

HIGH PERFORMANCE LED BATTEN











FEATURES

- > High output LEDs for up to 16 metre mounting height
- > Ideal for industrial and commercial applications
- > Wide beam or narrow beam versions available
- > Full range of gear options including dimmable, DALI and emergency available
- > CRI: Ra>80
- > Up to 113 lumens per Watt efficacy
- > 100,000 hours lifetime (L80/B10)

CONSTRUCTION

- > Extruded aluminium body finished in white (RAL 9010)
- > Polycarbonate extruded diffuser
- > Pressed steel spine with clip and fix
- > Polycarbonate end caps
- > Integral driver
- > Rear BESA fixings and cable entry
- > Supplied as standard with Wide beam (80°) clear lens
- > Supplied as standard with neutral white (4000K) LED

OPTIONS

/HFR High frequency analogue dimming /HFD Digital dimmable version /DALI DALI dimming control gear /M3 3 hours integrated emergency Emergency self test /AST /WW Warm white (3000K) Cool white (5000K) /CW /DL Daylight (6500K)

TO SPECIFY ORDER

High performance extruded aluminium LED batten as per MICRO LED XL

INSTALLATION NOTES

A range of mounting options including BESA fixing and wire suspension





HIGH PERFORMANCE LED BATTEN

Order Code	Description	lm	W	lm/W	A (mm)	B (mm)	C (mm)	kg
MLEDXL5950NW	84W - 4000K - Wide beam (80°) clear lens	9500	84	113	1414	62	75	4.2
MLEDXL51200NW	128W - 4000K - Wide beam (80°) clear lens	12000	128	94	1414	62	75	4.2



INDUSTRIAL - INDUSTRIAL AND COMMERCIAL APPLICATIONS









T. +44 1527 517 777

Park Farm Industrial Estate,

E. sales@tamlite.co.uk

W. tamlite.co.uk





