SOLAR S



High efficacy wall light

3 different models in range (small, large and halo)

Wall or ceiling mount for corridors and staircases



SOLAR S




- High efficacy wall light
- 3 different models in range (small, large and halo)
 Wall or ceiling mount for corridors and staircases
- Choice of white or satin chrome trim
- Integral sensor and emergency versions
- CRI: Ra>80
- Up to 120 lumens per Watt efficacy60,000 hours lifetime (L80/B20)









Modern LED wall light with small trim

Order Code	Description	lm	W	lm/W	kg
SLRS220NWW	19W - 4000K - White	2200	19	116	1.40
SLRS220NWSC	19W - 4000K - Satin chrome	2200	19	116	1.40
SLRS300NWW	25W - 4000K - White	3000	25	120	1.40
SLRS300NWSC	25W - 4000K - Satin chrome	3000	25	120	1.40

Dimensions

Order Code	Dia. (mm)	C (mm)
SLRS220NWW	330	72
SLRS220NWSC	330	72
SLRS300NWW	330	72
SLRS300NWSC	330	72









CONSTRUCTION

- Polycarbonate body finished in white (RAL 9010)
- Opal TP(a) diffuser
- Supplied as standard with neutral white (4000K) LED

OPTIONS


HFS	Microwave movement sensor
D	Dimmable DALI
M3	3 hours integrated emergency
A3	Emergency self test
D3	DALI self test

INSTALLATION NOTES

Wall or ceiling fix wired via rear or 20mm side knock-outs

TO SPECIFY

Circular IP65 white / opal bulkhead as per Tamlite SOLAR range



Lighting for a Living

Tamlite Lighting Sales Centre

Tamlite Field Sales Centre, Park Farm Industrial Estate, Redditch, Worcestershire, B98 0HU

T. 01527 517 777 E. sales@tamlite.co.uk W. tamlite.co.uk

Over 50 years lighting for a Living

As a UK manufacturer we have one of the widest lighting ranges across:















& Leisure







Healthcare

Industrial

Office

Sports

Urban

Communal

Education

Emergency