

CAPITAL S

Recessed module for SAS type ceilings



Features:

- Recessed module for SAS 330 ceiling types
- Also available for lay-in, plasterboard or Burgess type ceilings
- I-Tech microprism optic provides excellent glare control with BS EN-12464 compliance
- Suitable for office installations and general or task area lighting
- Available in 3 standard sizes with bespoke, retro-fit versions available
- Gear options of DALI and Emergency
- Air handling for 40 litres/second option

- CRI: Ra>80
- Up to 120 lumens per Watt efficacy
- 50,000 hours lifetime

Construction:

- Pressed steel body
- Prismatic polycarbonate diffuser
- Supplied as standard with neutral white (4000K) LED

Options:

- D - Dimmable DALI
- M3 - 3 hours integrated emergency
- A3 - Emergency self test
- D3 - DALI self test

CAPITAL S

Recessed module for SAS type ceilings

Order Codes

All dimensions are in millimetres

Order code	Description	Lumens (lm)	Total power (W)	Efficacy (lm/W)	Weight (kg)
CPS66MP300NW	25W - 4000K Microprism diffuser	3000	25	120	5.53
CPS123MP300NW	28W - 4000K Microprism diffuser	3000	28	107	6.19

Dimensions

All dimensions are in millimetres

Order code	A	B	C
CPS66MP300NW	626	595	98
CPS123MP300NW	1220	297	99

Installation instructions:

[View](#) or download the ceiling compatibility guide

To specify:

Recessed module for SAS type ceilings as per Tamlite CAPITAL S range

Please Note: Order codes listed are for standard (non-emergency) versions only. For all other gear options, please contact Tamlite Lighting.