

TBX

Tri-colour LED Batten



5 YR

IP20



Features:

Ideal retro-fit of existing T8 & T5 fixtures

Suitable for general use in industrial or commercial applications

Tri-colour easy switch technology from cool white (5000K) or neutral white (4000K) or warm white (3000K)

Available in standard or high outputs in 1200mm, 1500mm and 1800mm models

Also available with PIR

CRI: Ra>80

Up to 130 lumens per Watt efficacy

50,000 hours lifetime (L70/B50)

Construction:

Steel body finished in white (RAL 9010)

Polycarbonate extruded diffuser

Polycarbonate end caps

Integral driver

Options:

V205 - Batten-fit PIR

V206 - Batten-fit PIR and photocell

V208 - Batten-fit with daylight dimming

D - Dimmable DALI

D3 - DALI self test

M3 - 3 hours integrated emergency

A3 - Emergency self test

TBX

Tri-colour LED Batten

Order Codes


All dimensions are in millimetres

Order code	Description	Lumens (lm)	Total power (W)	Efficacy (lm/W)	Weight (kg)
TBX210TRI	10W - Tri-Colour - 600mm	1300	10	130	0.68
TBX417TRI	17W - Tri-Colour - 1200mm	2200	17	130	1.14
TBX528TRI	28W - Tri-Colour - 1500mm	3500	28	125	1.39
TBX631TRI	31W - Tri-Colour - 1800mm	3800	31	123	1.63
TBX556TRI	56W - Tri-Colour - 1500mm	6200	56	111	1.58
TBX662TRI	62W - Tri-Colour - 1800mm	7400	62	119	1.86

Dimensions

All dimensions are in millimetres

Order code	A	B	C
TBX210TRI	600	55	58
TBX417TRI	1200	55	58
TBX528TRI	1500	55	58
TBX631TRI	1800	55	58
TBX556TRI	1500	55	58
TBX662TRI	1800	55	58



Installation instructions:

Surface mount via rear entry BESA fixings or suspended via 3.0m wire suspension kit

To specify:

Compact Tri-colour
Batten as per Tamlite TBX range

Please Note: Order codes listed are for standard (non-emergency) versions only. For all other gear options, please contact Tamlite Lighting.