

ZENITH

Linear high output IP65 weatherproof for industrial areas



Features:

Suitable for industrial and warehousing areas up to 20m mounting height

Tamlite I-Tech optic designed for high optical control

Available in 3 outputs

IP20 Emergency option also available

CRI: Ra>80

Up to 153 lumens per Watt efficacy

50,000 hours lifetime

Construction:

Extruded aluminium body

Clear polycarbonate lens

Integral driver

Supplied as standard with neutral white (4000K) LED

Options:

M3 - 3 hours integrated emergency

ZENITH

Linear high output IP65 weatherproof for industrial areas

Order Codes


All dimensions are in millimetres

Order code	Description	Lumens (lm)	Total power (W)	Efficacy (lm/W)	Weight (kg)
ZNT4W1530NW	100W - 4000K - High/Low bay - Wide beam	15300	100	153	5.24
ZNT4W2040NW	150W - 4000K - High/Low bay - Wide beam	20400	150	136	5.24
ZNT4W2690NW	200W - 4000K - High/Low bay - Wide beam	26900	200	135	5.40

Dimensions

All dimensions are in millimetres

Order code	A	B	C
ZNT4W1530NW	1095	108	125
ZNT4W2040NW	1095	108	125
ZNT4W2690NW	1095	108	125



Installation instructions:

Fixed via end cap suspension holes supplied with 1.5m flex

To specify:

Linear high output weatherproof as per Tamlite ZENITH range

Please Note: Order codes listed are for standard (non-emergency) versions only. For all other gear options, please contact Tamlite Lighting.